

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 2250

IDENTITY: VELVA-SHEEN

Revision Date: 03/30/2014

=====

Section I

=====

Manufacturer's Name: Atlas Graham Ind. Co Ltd

Address: P.O. BOX 1978  
Winnipeg, MB R3H 0C5

Telephone Numbers:  
Emergency: 800/255-3924  
Information: 204-775-4451

=====

HMIS CODES: REACTIVITY: 1      FLAMMABILITY: 1      HEALTH: 1      PERSONAL PROTECT: A

=====

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV
1,8-P-MENTHADIENE	5989-27-5	NE	NE
ISOPARAFFINIC HYDROCARBON	64742-47-8	400 ppm	400 ppm
PROPANE/N-BUTANE	68476-86-8	N/A	1000ppm

=====

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	N/A	Specific Gravity (water=1)	0.89
Vapor Pressure(mm Hg)	11	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate (Butyl Acetate=1):	0.1
Solubility in Water:	100%		

Appearance and Odor: White foam, moderate citrus odor

=====

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):NONE      Flammable Limits: LEL: N/A      UEL: N/A

Extinguishing Media: Standard chemical fire extinguisher

Special Fire Fighting Procedures: Wear self contained breathing apparatus when indicated

Unusual Fire and Explosion Hazards: Contents under pressure. Exposure to temperatures above 120 F may cause bursting.

=====  
Section V: REACTIVITY DATA  
=====

PRODUCT NUMBER: 225000000-16AR

Stability: Stable: X Unstable: Conditions to avoid: Temperatures above 120 F  
Incompatibility (Materials to Avoid): Strong oxidizing agents, strong reducing agents.  
Hazardous Decomposition or Byproducts: Oxides of carbon  
Hazardous Polymerization: May Occur: Will Not Occur: X Conditions to Avoid: NONE

=====  
Section VI: HEALTH HAZARD DATA  
=====

Routes of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes

Health Hazards(Acute and Chronic):  
INHALATION: excessive exposure may cause slight dizziness.  
EYES: irritation and/or reddening.  
SKIN: may cause slight localized dryness if overexposed.  
INGESTION: may cause slight nausea.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Reg: No

Signs and Symptoms of Exposure: see health hazards above

Medical Conditions Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures:  
INHALATION: remove to fresh air. Consult physician.  
EYES: flush with water for 15 minutes. Consult physician if irritation persists.  
SKIN: wash with soap and water.  
INGESTION: drink several glasses of water and consult physician.

=====  
Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE  
=====

Steps to be Taken in Case Material is Released or Spilled: Wipe up with rag or use absorbent clay material. Dispose of residue in accordance with Federal, State and Local guidelines.

Waste Disposal Method: Do not puncture or incinerate container. Do not reuse container. Wrap container and place in trash collection.

Precautions to be Taken in Handling and Storing: Do not use or store near heat or open flame. Exposure to temperatures above 120 F may cause bursting.

Other Precautions: NONE

=====  
Section VIII: CONTROL MEASURES  
=====

Respiratory Protection: N/A  
Ventilation: Local Exhaust: Adequate  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves: N/A  
Eye Protection: Safety glasses are recommended when using chemical products  
Other Protective Clothing or Equipment: N/A  
Work/Hygienic Practices: Wash hands after using